










## Running machine h/p/cosmos mercury med 4.0 - Specifications



[ Picture with standard handrail and user terminal ]

-  [Operation](#)
-  [Standards / options / accessories](#)
-  [mercury med vs. quasar med](#)
-  [Specifications profile form](#)
-  [Printout \[ \\*.pdf \]](#)
-  [Specifications \[ \\*.txt \]](#)
-  [Gallery \[ \\*.gif / \\*.jpg / \\*.eps \]](#)
-  [Model overview](#)

Speed	0 ... 22 km/h / ... 6.1 m/s / ... 13.7 mph	medical	Running surface	150 x 50 cm / 59.0 x 19.7 inches
Elevation	0 ... 24 % / ... 13.5°		Track access height **	18 cm / 7.1 inches
Drive motor	2.2 kW / 3 hp		Device weight **	200 kg / 442 lbs
Power supply / Fuse	220 ... 240 V / 15 A optionally special voltage		Frame size **	210 x 82 x 136 cm 82.7 x 32.3 x 53.5 inches
Leakage current	0.2 mA *		max. load at surface	200 kg / 442 lbs
* Maximum leakage current in accordance to provision IEC EN 60601-1: 0.5 mA. ** Data for dimensions and weight of the device can deviate.			Live load p **	8.51 kN/m <sup>2</sup> / 868 kg/m <sup>2</sup> - dynamic (subject's weight 200 kg plus factor dynamic and safety coefficient)
h/p/cosmos running machines of the category medical meet the following technical safety standards and legal demands for medical application: MDD class <b>IIb</b> , <b>CE 0123</b> , IEC EN 60601-1, IEC EN 60601-1-2, IEC EN 60601-1-4, EN 957-1, EN 957-6 and VDE 0750/0751.		 According to EU-provisions it is prohibited to place on market sports running machines in the medical field.		

order number	
h/p/cosmos mercury med 4.0	cos0C297080000