










Running machine h/p/cosmos quasar 4.0 - Specifications



[Picture with standard handrail and user terminal]

-  [Operation](#)
-  [Standards / options / accessories](#)
-  [quasar vs. mercury](#)
-  [Specifications profile form](#)
-  [Printout \[*.pdf \]](#)
-  [Specifications \[*.txt \]](#)
-  [Gallery \[*.gif / *.jpg / *.eps \]](#)
-  [Model overview](#)

Speed	0 ... 25 km/h / ... 6.9 m/s / ... 15.5 mph	sports	Running surface	170 x 65 cm / 66.0 x 25.6 inches
Elevation	0 ... 28 % / ... 15.6°		Track access height **	23 cm / 9.0 inches
Drive motor	2.2 kW / 3 hp		Device weight **	370 kg / 818 lbs
Power supply Fuse	220 ... 240 V / 15 A optionally special voltage		Frame size **	230 x 105 x 140 cm 90.6 x 41.3 x 55.1 inches
Leakage current	4.5 mA *		max. load at surface	200 kg / 442 lbs
* Maximum leakage current in accordance to provision IEC EN 60601-1: 0.5 mA. ** Data of dimension and weight of the device can deviate.			Live load p **	7.00 kN/m ² / 713 kg/m ² - dynamic (subject's weight 200 kg plus factor dynamic and safety coefficient)
h/p/cosmos sports devices meet the following technical safety standards and legal demands for sports application: CE , IEC EN 60335-1, EN 957-1 and EN 957-6 as well as VDE 0700/0701.			 According to EU-provisions it is prohibited to place on market sports running machines in the medical field.	

order number	
h/p/cosmos quasar 4.0	cos01001100000