














Running machine series h/p/cosmos venus 4.0 - Specifications



-  [Dimensions / Weights](#)
-  [Standards / options / accessories](#)
-  [Operation](#)
-  [References](#)
-  [Printout](#) [*.pdf]
-  [Gallery](#) [*.gif / *.jpg / *.eps]
-  [Download of specification files](#)
Click on  in front of the model name ...

Speed	0 ... 40 km/h / ... 11.1 m/s / ... 24.9 mph	medical	Running surface	see dimensions
Elevation	- 35 ... + 35 % / ... 19.0°		Track access height **	45 cm / 17.7 inches
Drive motor	5.5 kW / 7 hp		Device weight **	see dimensions
Power supply	3 x 400 V / Fuse 32 A		Frame size **	see dimensions
Leakage current	0.25 mA *		max. load at surface	280 kg / 619 lbs
* Maximum leakage current in accordance to provision IEC EN 60601-1: 0.5 mA. ** Data of dimension and weight of the device can deviate.			Live load p **	7.37 kN/m ² / 751 kg/m ² - dynamic (subject's weight 200 kg plus factor dynamic and safety coefficient)
h/p/cosmos running machines of the category medical meet the following technical safety standards and legal demands for medical application: MDD class IIb , CE 0123 , IEC EN 60601-1, IEC EN 60601-1-2, IEC EN 60601-1-4, EN 957-1, EN 957-6 and VDE 0750/0751.		 According to EU-provisions it is prohibited to place on market sports running machines in the medical field.		

order numbers [r = for cycling and wheel chair applications]

 h/p/cosmos venus 4.0 200/75	cos09001050000
 h/p/cosmos venus 4.0 200/75r	cos09201050000
 h/p/cosmos venus 4.0 200/100	cos09401050000
 h/p/cosmos venus 4.0 200/100r	cos09601050000